

(19)



JAPANESE PATENT OFFICE

## PATENT ABSTRACTS OF JAPAN

(11) Publication number: **10100479 A**(43) Date of publication of application: **21 . 04 . 98**

(51) Int. Cl.

**B41J 2/52**  
**H04N 1/405**  
**H04N 1/60**  
**H04N 1/52**

(21) Application number: **09253401**(22) Date of filing: **18 . 09 . 97**(30) Priority: **20 . 09 . 96 US 96 716950**(71) Applicant: **SEIKO EPSON CORP**(72) Inventor: **CHASHIN LEE**  
**JOSEPH SHEW**

(54) **METHOD AND SYSTEM FOR GENERATING**  
**HALF TONE IMAGE AND COMPUTER**  
**PROGRAM PRODUCT**

COPYRIGHT: (C)1998,JPO

(57) Abstract:

**PROBLEM TO BE SOLVED:** To reduce the quantity of ink to be used in a printer by defining holes to be not printed in a concentrated dot type dither matrix and arranging these holes in a relatively large dispersed distributed matrix in the concentrated dot type dither matrix.

**SOLUTION:** A reduced ink matrix 61 defines a region, i.e., a hole, in a dither matrix 53. A hole in a dither matrix 53 defines a region in a halftone image 54 which is not printed with ink under any conditions. In order to prevent the halftone image 54 from exhibiting a rough granular appearance in an image region having a relatively bright color tone, multiple holes are prevented from existing in the dither matrix 53. The reduced ink matrix 61 can be provided as a random dither matrix, e.g. a dispersed dot type dither matrix or a Bayer type matrix.

